

Booster Alk

Alkaline Degreaser Cleaner

Item Code: 00034688

Booster Alk is a strong alkaline stain remover cleaner specifically designed for removing stains, streaks, dirt and grease. Booster Alk is the specific ally for the most stubborn dirt, such as treatment residues and epoxy residues. It is a concentrated product to be diluted in water as a detergent. Booster Alk is also a specific stain remover for removing stubborn dirt from the porosity of the material. Given its strong performance, it is mainly suitable for the industrial sector. Also recommended for stains whose origin is unknown.



MAIN PLUSES

- Extra strong alkaline degreaser
- Deep cleans
- Quickly removes layered grease
- Removes stains from blackened floors (tyres, foot traffic)
- Eliminates epoxy residues

MATERIALS



Natural
stone



Quartz



Ceramics



Water Base

SECONDARY PLUSES

- Extraordinary cleaning of organic and inorganic stains
- Removes waxes
- Removes stains from water, wine, cola, coffee, daily food dirt, fingerprints
- Respects steel joints and profiles
- Pleasant fragrance

BEFORE AND AFTER APPLICATION



TECHNICAL FEATURES

The product is pleasantly scented and colorful. Concentrated product to be diluted in water as a detergent and pickling. Also used as a stain remover on ceramics and porcelain stoneware.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.

DECLARATIONS

n.a.

INSTRUCTIONS FOR USE

Booster Alk is a concentrated product. Dilute in water and apply the solution to the surface, leave it on for 5-10 minutes, then clean with a single brush and brush. Finally, remove residues with a wet vacuum cleaner and rinse with plenty of water.

To remove stains and/or epoxy residues on ceramics: apply the product pure, leave it on for 10-20 minutes and clean with a brush. For stubborn stains, we suggest covering with plastic foil and leaving it on for several hours. The product may change the appearance of some plastic materials and alkali-sensitive surfaces. Do not use on porous surfaces, treated with shiny waxes, as the protection may be removed. On a clean and dry surface, it is recommended to apply a Tenax stain protection device.

If the surface is being treated for the first time, it is a good idea to evaluate the effect and tightness of the tile on a sample or on a hidden corner. After use, close the package tightly.

Detergents: dilute the product with water in the ratio of 1:10 to 1:20 depending on the degree of soiling. Dilute with water in a ratio of 1:5 for stubborn dirt. Removal of difficult stains: use the product pure (as is).

TECHNICAL DATA	
Density at 25°C	1,020 Kg/L
pH	12
Appearance	Liquid
Color	Light yellow

STORAGE AND SHELF LIFE

Under normal conditions of use and work (between 5 and 30 °C), the product is well stored away from sources of heat, humidity and direct sunlight and is guaranteed for 24 months. Reseal the package carefully after use. Protect the product from frost.

SAFETY PRECAUTIONS

It is a chemical. Before use, it is recommended to read the safety data sheet and the notes on the jars/drums.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.