

Liquido Trasparente

Item Code: 00034642

Liquido Trasparente polyester mastic for bonding, repairs and grouting.

Liquido Trasparente is a low-viscosity mastic, used for bonding and repairing marble, natural stone and quartz. It can also be used for grouting and repairing imperfections. The product is easy to apply and can be spatulated even at low temperatures.

After polymerization, it is dry, well polishable and easily sanded.

It is characterized by its high cold reactivity, low shrinkage and excellent adhesion on marble, stone and quartz agglomerates.



MAIN FEATURES

- High adhesion
- Fast hardening
- Easily penetrates imperfections

MATERIALS



Natural
stone



Quartz

SECONDARY FEATURES

- Very bright
- Low shrinkage
- Easily to polish
- Easy to color
- Suitable for back-slab reinforcement

TECHNICAL FEATURES

Transparent liquid polyester mastic for repairing, filling and gluing marble, stone and agglomerates.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.

DECLARATIONS

n.a.

INSTRUCTIONS FOR USE

Before applying the product, make sure that the material is clean, dry and free of dust. Take the necessary amount of mastic from the container and add 2-3% of hardener paste, mix vigorously and proceed with use. Never put the putty mixed with the hardener back into the container. To correct the color of the mastic, use coloring pastes for polyester or metal oxides, before the hardener adding a quantity necessary to obtain the desired color, then complete with the catalyst to obtain the hardening. The color must be evaluated after hardening. An excess of coloring paste or powdered pigments could alter the final characteristics of the mastic. Close containers after use.

TECHNICAL DATA

Viscosity 25°C (ASTM D2196)	1250-2450 cP
Density at 25° kg/L	1.1
Aspect	Transparent liquid
Mastic + hardener ratio	100 + 2/3
Gel time in bulk at 25°C	5' - 8'
Thin layer tacky free time at 25°C	25'
Recommended workability time at 25°C	60' - 80'
Minimum reaction temperature	0°C
Minimum temperature of use after curing	0°C
Maximum temperature of use after curing	+110°
Storage stability 18-25°C	12 months
Adhesion on white marble after 2h (CQ26 method)	n.a.
Adhesion on white marble after post curing at 50°C for 12 h (CQ26 method)	n.a.
Adhesion on quartz after 2h (CQ26 method)	n.a.
Adhesion on quartz after post curing at 50°C for 12 h (CQ26 method)	n.a.

*rupture of the support

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.

STORAGE

The product is well stored between 18-25°C away from heat, humidity, direct sunlight and in the original closed and unused containers and is guaranteed for 12 months.

SAFETY PRECAUTIONS

Mastic and hardener are chemicals. Before use, it is recommended to read the safety data sheets and notes on the label on the containers or drums.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.