

Solido

Item Code: 00034623

Coloured solid polyester mastic for bonding, repairing and laminating.

Solido is a thixotropic mastic that does not lose its verticality, maintaining its consistency even on vertical surfaces. It is available in a wide range of colours and is suitable for bonding and repairing marble, natural stone and quartz. It can also be used for grouting and to correct imperfections.

The product is easy to apply thanks to its soft consistency and excellent spreadability, it maintains its stability during use. Once cured, the mastic is dry, easily polished and sanded. Solid, it stands out for its excellent adhesion and high polishability.



MAIN FEATURES

- Strong bonding
- Soft and easy to spatulate
- Low yellowing

MATERIALS



Natural
stone



Quartz

SECONDARY FEATURES

- Very bright
- Low shrinkage
- Easy to polish
- Easy to color

TECHNICAL FEATURES

Solid coloured polyester mastic for repairing, grouting and gluing marble, stone and agglomerates.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.

DECLARATIONS

n.a.

INSTRUCTIONS FOR USE

Before applying the product, make sure that the material is clean, dry and free of dust. Take the necessary amount of mastic from the container and add 2-3% of hardener paste, mix vigorously and proceed with use. Never put the putty mixed with the hardener back into the container. To correct the color of the mastic, use coloring pastes for polyester or metal oxides, before the hardener adding a quantity necessary to obtain the desired color, then complete with the catalyst to obtain the hardening. The color must be evaluated after hardening. An excess of coloring paste or powdered pigments could alter the final characteristics of the mastic. Close containers after use.

TECHNICAL DATA

Viscosity 25°C	Thixotropic paste
Density at 25° Kg / L	1.65
Aspect	Colored paste
Mastic + hardener ratio	100 + 2/3
Gel time in bulk at 25°C	3' - 4'
Thin layer tacky free time at 25°C	25' - 30'
Recommended workability time at 25°C	60' - 80'
Minimum reaction temperature	0°C
Minimum temperature of use after curing	0°C
Maximum temperature of use after curing	+110°
Storage stability 18-25°C	12 months
Adhesion on white marble after 2h (CQ26 method)	n.a.
Adhesion on white marble after curing at 50°C for 12h (CQ26 method)	n.a.
Adhesion on quartz after 2h (CQ26 method)	n.a.
Adhesion on quartz after curing at 50°C for 12h (CQ26 method)	n.a.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.

STORAGE AND SHELF LIFE

The product is well stored between 18-25°C away from heat, humidity, direct sunlight and in the original closed and unused containers and is guaranteed for 12 months.

SAFETY PRECAUTIONS

Mastic and catalyst are chemicals. Before use, it is recommended to read the safety data sheets and notes on the label on the containers or drums.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.