

Ager FS

Solvent-based protective water and oil repellent treatment – wet-look effect

Ager FS is a solvent-based stain-resistant color-enhancing product, ideal for marble, travertine, natural stone, granite, and quartz agglomerates. It is designed to achieve a wet-look finish and can be used both indoor and outdoor. For a more pronounced and long-lasting effect, application is recommended on rough, sandblasted, brushed, flamed, or honed surfaces.

Ager FS penetrates and bonds to the microporosities of the material, providing the treated surface with excellent water and oil repellent properties. It also offers antigraffiti protection and does not yellow when exposed to sunlight.



MAIN FEATURES

- Water- and oil-repellent enhancer, wet-look effect
- Deep penetration
- Maximum protection
- Long-lasting performance

SURFACES



Natural Stone Quartz



Solvent Based



Food Safety Declaration

REF. DM 21/03/1973 -
Reg. UE 10/2011

SECONDARY FEATURES

- Does not form surface films
- Allows the material to breathe
- Suitable for indoor and outdoor applications
- Facilitates cleaning

BEFORE AND AFTER APPLICATION

n.d.

TECHNICAL FEATURES

Solvent-based penetrating product with strong revitalizing properties.

It penetrates into the microporosities of the material, creating a barrier against dirt and stains.

PRODUCT FOR PROFESSIONAL USE ONLY

The information included in the present technical data sheet are based on tests carried on in our laboratory and are correct, based on our experience. The present data can be changed without notice and shall not be considered legally relevant. It is under the responsibility of the customer to verify the suitability of the product before use. It is obligation of the customer to verify that the use of the product is done according to laws, legislation, patents of the customer's country.

DECLARATIONS

Solvent-based impregnating product. Does not leave a surface film. Specifically designed for porous materials. Once applied as indicated in the 'Instructions for Use' section, Ager FS complies with the global migration limits set forth in DM 21/03/1973 and EU Regulation 10/2011.

INSTRUCTIONS FOR USE

Ager FS must be applied on clean, dry surfaces. The presence of residual water and/or dirt may cause uneven absorption. Apply the treatment on a surface not directly exposed to sunlight, with a temperature between 10°C and 30°C. The complete absorption of the product into the material is influenced by temperature: at around 10°C absorption times will be longer, while at around 30°C absorption will be faster. It is recommended to apply the product to small, delimited areas, working step by step. The product can be applied with a brush, cloth, or airless sprayer.

Before treating the entire surface, test on a small area to check the absorption level and evaluate the final result. Apply the product until the material is fully saturated. A few minutes after application, spread the product evenly with circular movements and remove any unabsorbed excess with a clean cloth, avoiding the formation of a surface film. It is advisable to repeat the application after approximately 20 minutes.

Allow 24 hours to achieve full protection of the material and stain resistance. If the product is applied on flooring, wait 24 hours before using the surface.

TECHNICAL DATA

Density at 25°C	0.995 kg / L
Aspect	Transparent liquid
Color	Light yellow

COVERAGE

Consumption largely depends on the material porosity.

INDICATIVE COVERAGE WITH 1 L OF PRODUCT:

SURFACES WITH LOW POROSITY (such as, dense or polished surfaces)	30 - 40 m ² 323 - 430 sqft
SURFACES WITH HIGH POROSITY (such as, polished or brushed surfaces)	20 - 30 m ² 215 - 323 sqft

STORAGE E SHELF LIFE

The product has an estimated shelf life of 24 months when stored between 5°C and 30°C. Keep the product away from sources of heat, moisture, and direct sunlight. Reseal the container after use.

Protect the product from temperatures below 0°C.

SAFETY MEASURES

Ager FS is a chemical product. Before using it, it is recommended to read the safety data sheet and the instructions on the containers or drums.

PRODUCT FOR PROFESSIONAL USE ONLY

The information included in the present technical data sheet are based on tests carried on in our laboratory and are correct, based on our experience. The present data can be changed without notice and shall not be considered legally relevant. It is under the responsibility of the customer to verify the suitability of the product before use. It is obligation of the customer to verify that the use of the product is done according to laws, legislation, patents of the customer's country.