

Antislip M

Item Code: 00034588

Water-based anti-slip treatment for marble and marble agglomerates

Antislip M is a water-based anti-slip treatment, specific for marble and marble agglomerate surfaces. The product has a definitive and irreversible effect. Thanks to the synergistic action of an acid component and a nano-silicate component, it acts quickly on the surface. The product is easy to use and has short application times. Antislip M does not form a surface film and acts definitively, creating an anti-slip effect on the treated material.



MAIN PLUSES

- Permanent anti-slip effect
- Leaves no surface residue
- Recommended on stairs, entrances, pool edges

MATERIALS



Natural stone Agglomerate

Water-based

SECONDARY PLUSES

- Effective even on damp surfaces
- Indoor and outdoor
- Does not require periodic application
- Leaves no residue

BEFORE AND AFTER APPLICATION

n.a.

TECHNICAL FEATURES

The product is a water-based acid descaler that alters surfaces making them porous. Ready to use.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.

DECLARATIONS

n.a.

INSTRUCTIONS FOR USE

Antislip M should be applied evenly on a dry, clean surface. A rag or a brush can be used to apply the product. Leave Antislip M on for 1 to 5 minutes, then rinse thoroughly with clean water.

If you are not satisfied with the result, you can repeat the application. Each material can react differently, with contact times also varying depending on the finish. For example, a glossy surface may require less contact time, especially if you want to achieve a slight anti-slip effect while maintaining as much of the original shine as possible.

The product can reduce the degree of gloss, which is why it is recommended to test it first on a sample or hidden area to assess its final effect.

IMPORTANT: This is an irreversible treatment.

TECHNICAL DATA	
Density at 25°C	1,080 kg/L
Appearance	Transparent liquid
pH	2,3
Color	Colorless

COVERAGE	
Consumption depends on the porosity of the material.	
INDICATIVE COVERAGE WITH 1L OF PRODUCT:	
INDICATIVE CONSUMPTION	30-40 m2 323 - 430 sq.ft.

STORAGE AND SHELF LIFE

The product has an estimated shelf-life of 24 months in storage conditions between 5 and 30 °C. Keep the product away from heat, moisture, and direct sunlight. Close the package after use.

Protect the product from temperatures below 0°C.

SAFETY PRECAUTIONS

Antislip M is a chemical product. Before use, it is recommended to read the safety data sheet and the notes on the jars or drums.

PRODUCT FOR PROFESSIONAL USE ONLY

The information contained in this data sheet is based on tests carried out in our laboratories and is correct based on our experiences. This data may be changed without prior notice and is not to be considered legally relevant. It is the customer's responsibility to check the suitability of the product before use. It is the customer's obligation to verify that the use of the product complies with the laws, regulations and patents in force in the country in use.