

Proseal FS

NATURAL EFFECT IMPREGNATOR SEALER

Natural effect impregnator sealer. Its high penetration capacity and resistance to weathering make it ideal for high and long-lasting protection of surfaces. The product complies with the global migration limits referred to Regulations DM 21/03/1973 and EU Regulations 10/2011.

Untreated



Treated



MAXIMUM LONG-LASTING PROTECTION



PENETRATES DEEPLY



IDEAL FOR KITCHENTOP

Technical data:

- ◆ **Density at 25°C kg/l:** 0.820
- ◆ **Standard colour:** colourless
- ◆ **Appearance:** opalescent liquid

Indicative duration:

- ◆ **Indoor:**
12-24 months
- ◆ **Outdoor:**
6-12 months

The stated consumption is merely indicative



Solvent based



Food safety declaration

DM 21/03/1973 - Reg. UE 10/2011



**Indoor
Outdoor**

Tools:

- ◆ Brush
- ◆ Cloth
- ◆ Sponge
- ◆ Spray nebulizer

How to apply it:

- ◆ Apply the product to a dry, clean surface.
- ◆ Apply the product evenly.
- ◆ Do not direct expose to sunlight during application.
- ◆ After a few minutes, wipe off excess product with a clean cloth.
- ◆ Do not step on the treated surface for 4-6 hours.
- ◆ The material will achieve the desired protection after 24 hours.



Natural stone



Quartz

Indicative consumption 1 l:

Consumption depends on the porosity of the material

Lava stone and marble 30-40m²

Quartz 20-30m²

Safety measures:

Read the instructions in the technical and safety data sheet and the notes on the packaging before use. Close the container after use. For professional use only.

Warnings:

When a surface is treated for the first time, it is advisable to evaluate the effect or adhesion on a sample or hidden corner.