

Antislip M

ANTI-SLIP TREATMENT FOR MARBLE

Definitive anti-slip treatment for marble. The water-based product makes the floor safe flooring even in wet conditions, without creating a surface film and without leaving any residue.



DEFINITIVE

DOES NOT CREATE SURFACE
FILMEFFECTIVE EVEN IN
WET CONDITIONS

Technical data:

- ◆ **Density at 25°C gr/cm3:** 1,080
- ◆ **Standard colour:** yellow
- ◆ **Appearance:** opalescent liquid

Indicative duration:

- ◆ **Indoor:** permanent
- ◆ **Outdoor:** permanent

The stated duration is approximate



Water based

Indoor
Outdoor

Tools:

- ◆ Brush
- ◆ Cloth
- ◆ Sponge
- ◆ Fleece



Natural stone

How to apply it:

- ◆ Apply the product to a dry, clean surface.
- ◆ Apply the product evenly.
- ◆ Do not expose to sunlight during application.
- ◆ If applied improperly, a sticky film will form.
- ◆ After a few minutes, wipe off excess product with a clean cloth.
- ◆ Do not step on the treated surface for 4-6 hours.
- ◆ After 24 hours, the treatment will be absorbed by the material, achieving the desired protection.
- ◆ Ideal for stairs, entrances, swimming pools, both indoors and outdoors.

Indicative consumption 1 l:

Consumption depends on the porosity
of the material - yield per coat

Lava stone and marble	30-40m2
Quartz	20-30m2

Safety measures:

Read the instructions in the technical and safety data sheet and the notes on the packaging before use. Close the container after use. For professional use only.

Warnings:

When a surface is treated for the first time, it is advisable to evaluate the effect or adhesion on a sample or hidden corner.



Opening the can



Dampen the cloth



Apply the product to the surface



Ensure that the product is applied evenly



Final result



Assess whether the grip obtained is satisfactory or reapply the product