

Tixo XE

TRANSPARENT SOLID POLYESTER MASTIC

Strong and ultra-fast transparent mastic with low yellowing. Soft and easy to spread, it does not lose verticality and is ideal for visible bonding, lamination and repairs.



 **STRONG AND ULTRA-FAST BONDING**

 **SOFT**

 **EXCELLENT SPREADABILITY**

Technical data:

- ◆ **Density at 25° gr/cm³:** 1.1
- ◆ **Standard colour:** transparent
- ◆ **Appearance:** yellowish paste

Approximate consumption:

- ◆ **For grouting:**
20-30 linear meters
- ◆ **For bonding:**
30-40 mt2

The stated duration is only approximate



Natural stone



Quartz

How to apply it:

- ◆ Remove the desired quantity of product from the container and weigh it.
- ◆ Comply with the ratio between the product and its hardener as indicated in the TDS.
- ◆ Use clean tools when mixing.
- ◆ If necessary, add liquid or pigment dyes before mixing with the hardener.
- ◆ Make sure that the material on which the product will be applied is clean and dry.
- ◆ To clean tools soiled with mastics, use non-greasy solvents, e.g. Acetone or Butyl Acetate. Use the necessary PPE.
- ◆ Read the technical and safety data sheet carefully.
- ◆ Close the containers with their original caps for correct storage.
- ◆ Avoid prolonged contact with air.

Performance:

Adhesion strength [Mpa]	marble 4.0
Gel time in mass at 25°C	2-5 min
Workability time at 25°C	35-50 min
Extraclear	no
Stability to sunlight	good
Wet effect	good
Spreadability	good
Adhesion on wet	no

Safety measures:

Before use, please read the instructions in the safety data sheet and the notes on the packaging. Close the container after use. For professional use only.

Warnings:

When a surface is treated for the first time, it is advisable to evaluate its effect or adhesion on a sample or hidden corner.